

Serie CORTR



NEW



Code Tank	Capacity LT	Ø Effective mm	H TOT mm	F mm	V mm
200A	222	650	820	1,5	1,5
300A	339	650	1170	1,5	1,5
550	552	790	1170	1,5	1,5
330	330	1000	670	1,5	1,5
700	722	1000	1170	1,5	1,5
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—



Coperchio parapolvere
Anti dust cover
Couvercle cache poussiere



Valvole e rubinetteria inox
S/S valves and taps
Valves et robinets inox



Portelle
Manholes
Portes



Assaggiavino
S/S sample tap
Degustateur inox



Termometro
Thermometer
Thermometre




Segnalivello
Level gauge
Regle de niveau


Caratteristiche costruttive



AISI 304
AISI 316 optional



Finitura esterna fioretata o satinata
External marbled or satin polished
Finition exterieure bouchonnée ou brossée



Saldature TIG decapate e spazzolate
TIG welding pickled and passivated
Nettoyage mecanique de soudures TIG



Fondo bombato riscaldato (optional)
Heated roundly bottom (optional)
Chauffé fond bombé (optional)