

# Serie SPABPTR



NEW



Code Tank	Capacity LT	Ø Effective mm	HV mm	P		H TOT mm	F mm	V mm
				n°	hp			
300	313	650	1000	3	330	1330	1,5	1,5
400A	424	650	1300	3	330	1630	1,5	1,5
500	514	790	1100	3	400	1500	1,5	1,5
600	612	790	1300	3	400	1700	1,5	1,5
700	710	790	1500	3	400	1900	1,5	1,5
750	743	1000	1000	3	400	1400	1,5	1,5
1000	979	1000	1300	3	400	1700	1,5	1,5
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—



Piedi regolabili  
Adjustable feet  
Pieds réglables



Valvole e rubinetteria inox  
S/S valves and taps  
Valves et robinets inox



Portelle  
Manholes  
Portes



Assaggiavino  
S/S sample tap  
Degustateur inox



Termometro  
Thermometer  
Thermometre



Segnalivello  
Level gauge  
Regle de niveau


## Caratteristiche costruttive



AISI 304  
AISI 316 optional



Finitura esterna fiorettrata o satinata  
External marbled or satin polished  
Finition extérieure bouchonnée ou brossée



Saldature TIG decapate e spazzolate  
TIG welding pickled and passivated  
Nettoyage mécanique de soudures TIG



Fondo bombato riscaldato (optional)  
Heated roundly bottom (optional)  
Chauffé fond bombé (optional)