

Serie SPATR

NEW



Code Tank	Capacity LT	Ø Effective mm	H TOT mm	F mm	V mm
200B	189	650	650	1	1,5
300	305	650	1000	1	1,5
400A	405	650	1300	1	1,5
500	500	790	1000	1	1,5
600	598	790	1300	1	1,5
700	696	790	1500	1	1,5
750	722	1000	1000	1,2	1,5
1000	958	1000	1300	1,2	1,5
—	—	—	—	—	—
—	—	—	—	—	—



Baggiolo inox
S/S stand
Socle inox



Valvole e rubinetteria inox
S/S valves and taps
Valves et robinets inox



Portelle
Manholes
Portes



Assaggiavino
S/S sample tap
Degustateur inox




Termometro
Thermometer
Thermometre




Segnalivello
Level gauge
Regle de niveau


Caratteristiche costruttive



AISI 304
AISI 316 optional



Finitura esterna fiorettrata o satinata
External marbled or satin polished
Finition exterieure bouchonnée ou brossée



Saldature TIG decapate e spazzolate
TIG welding pickled and passivated
Nettoyage mecanique de soudures TIG

LT.

Capacità fino a 1000 lt
Capacity until 1000 lt
Capacité jusqu'à 1000 lt