

# Serie STOCTR

NEW



Code Tank	Capacity LT	Ø Effective mm	HV mm	P		H TOT mm	F mm	V mm
				n°	hp			
350	351	650	1000	3	330	1580	1,5	1,5
450A	450	650	1300	3	330	1880	1,5	1,5
550	572	790	1100	3	400	1750	1,5	1,5
650	670	790	1300	3	400	1950	1,5	1,5
750	768	790	1500	3	400	2150	1,5	1,5
1000	1096	1000	1300	3	400	1975	1,5	1,5
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—



Piedi regolabili  
Adjustable feet  
Pieds réglables



Valvole e rubinetteria inox  
S/S valves and taps  
Valves et robinets inox



Portelle e chiusini  
Portelle  
Portelle



Assaggiavino  
S/S sample tap  
Degustateur inox



Termometro  
Thermometer  
Thermometre




Segnalivello  
Level gauge  
Regle de niveau


## Caratteristiche costruttive



AISI 304  
AISI 316 optional



Finitura esterna fiorettrata o satinata  
External marbled or satin polished  
Finition extérieure bouchonnée ou brossée



Saldature TIG decapate e spazzolate  
TIG welding pickled and passivated  
Nettoyage mécanique de soudures TIG



Fondo conico riscaldato (optional)  
Heated conical bottom (optional)  
Chauffé fond conique (optional)