

Serie STOBPTR



NEW



Code Tank	Capacity LT	Ø Effective mm	HV mm	P		H TOT mm	F mm	V mm
				n°	hp			
350	351	650	1000	3	330	1580	1,5	1,5
450A	450	650	1300	3	330	1880	1,5	1,5
550	572	790	1100	3	400	1750	1,5	1,5
650	670	790	1300	3	400	1950	1,5	1,5
750	768	790	1500	3	400	2150	1,5	1,5
1000	1096	1000	1300	3	400	1975	1,5	1,5
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—



Piedi regolabili
Adjustable feet
Pieds réglables



Valvole e rubinetteria inox
S/S valves and taps
Valves et robinets inox



Portelle e chiusini
Portelle
Portelle



Assaggiavino
S/S sample tap
Degustateur inox



Termometro
Thermometer
Thermometre



Segnalivello
Level gauge
Regle de niveau


Caratteristiche costruttive



AISI 304
AISI 316 optional



Finitura esterna fiorettrata o satinata
External marbled or satin polished
Finition extérieure bouchonnée ou brossée



Saldature TIG decapate e spazzolate
TIG welding pickled and passivated
Nettoyage mecanique de soudures TIG



Fondo bombato riscaldato (optional)
Heated roundly bottom (optional)
Chauffé fond bombé (optional)